

Stealth II CONTINUOUS MOTION CARTONER



The Stealth II continuous motion cartoner from MGS Machine uses a rotary arm to dispense flattened cardboard cartons before erecting them and filling them with a variety of different products.

The pharmaceutical cartoning system can operate continuously without human labour, increasing output significantly.

FEATURES

- Small footprint requires less floor space.
- Simplified user and diagnostic mode accessed through on screen display
- Servo-based design means fewer moving parts reducing maintenance and providing greater accuracy at high speeds.
- Pre-designed infeed solutions provides for flexibility in handling tubes, vials, bottles, pouches, etc as well as literature insertion.
- Powered carton magazine is ergonomically correct and loads easily.
- Unique guard scheme allows for walk-in access to the machine for cleaning, maintenance and changeover.
- Standard carton pre-break eliminates carton setup failures.
- No tool, quick change carton set-up masks, drop-in plows and guides and HMI recipes reduce changeover time.
- Fall-through containment shelving and guarding design for easy access and clear sight lines.
- Construction fully supports ANSI/PMMA B1.55.1-2006 safety and cGMP guidelines.
- Pharmaceutical validation assistance is included.



IMPACT AUTOMATION SOLUTIONS

Unit 2 • 52 Holker St Silverwater NSW 2128 Australia • T +61 (0)2 9648 6000 W www.impactautomation.com.au
Agents for: MGS, Lakewood Process Machinery, AZCO, A-One Packaging, Modular Packaging

Stealth II CONTINUOUS MOTION CARTONER



OPTIONAL FEATURES



- Automatic product handling/collating
- Insert feeding
- Coding/Printing
- Bar code verification
- Open flap detection
- Vision verification
- Vision integrated with HMI
- Cam in OR adjustable infeed buckets
- Transferable batch record file
- Remote diagnostic unit

CARTON STYLES

- Economy or FOL Glue End
- Straight tuck
- Reverse tuck
- Airplane tuck
- Fifth panel cartons

SPECIFICATIONS

- OUTPUT: Up to 400 CPM
- POWER: 230VAC, 3 phase, 50-60hz
- AIR: 5 SCFM @ 80 PSI
- MAGAZINE: 72" long, powered, horizontal



Centers	Length	Width	Depth	Max Speed
3"	.75 - 1.88 in 19 - 48mm	.38 - 3.00 in 9.5 - 76mm	2.25 - 6.50 in 57 - 165mm	400 CPM
4.50"	.75 - 3.38 in 19 - 86mm	.38 - 3.00 in 9.5 - 76mm	2.25 - 6.50 in 57 - 165mm	325 CPM
6"	.75 - 4.0 in 19 - 100mm	.38 - 3.00 in 9.5 - 76mm	2.25 - 6.50 in 57 - 165mm	250 CPM



IMPACT AUTOMATION SOLUTIONS

Unit 2 • 52 Holker St Silverwater NSW 2128 Australia • T +61 (0)2 9648 6000 W www.impactautomation.com.au
Agents for: MGS, Lakewood Process Machinery, AZCO, A-One Packaging, Modular Packaging